SoundEar 2 Outdoor Noise Warning Sign



Features

- Weatherproof outdoor noise activated sign
- Lights up when noise levels are too high
- Green = Monitoring : Yellow = Getting loud : Red
 Too loud
- Adjustable trigger level from 40 to 115 dB(A)

Applications

- Outdoor noise level warning
- Areas exposed to rain or snow
- Dusty environments
- Locations requiring extra physical protection

Outdoor Noise Warning Sign

The SoundEar 2 Outdoor is a noise activated sign for use outdoors, in any weather, and is also suitable for use in environments with high levels of dust. It provides an immediate warning of high noise levels.

Modes of Operation

Similar to other noise warning signs in the SoundEar range, this sign can be configured to light up at your chosen sound level. The green light is on all the time, to remind people that the level of noise is important. The yellow light indicates that the noise levels are getting close to the limit. The red light comes on to warn that the levels are too high.

If you need data logging and software then please see the SoundEar 3 Outdoor Noise Sign.

Weather Protection

The SoundEar 2 Outdoor consists of a standard SoundEar 2 Noise Warning Sign fitted inside a wall-mountable weatherproof case. A microphone is mounted on the base of the enclosure, fitted with a suitable windshield. A power cable also enters the bottom of the enclosure.

Setting the Noise Limit

The dial to set level at which the sign lights up red is hidden inside the weatherproof enclosure, making it difficult to tamper with. With the front cover removed the sign can be lifted slightly giving access to the dial.

The adjustments for the red light are made in 5 dB steps from 40 to 115 dB(A). The yellow lights come on 5 dB below the red light as a warning that the noise levels are getting high.

NoiseMeters

SoundEar 2 Outdoor Noise Warning Sign

Specifications

Technical Specifications

Frequency

20Hz to 16kHz

Range

Trigger Range

40 to 115 dB in 5 dB steps

Deviation Frequency ±3 dB "A"

Weighting

Time Weighting Slow

Cabinet

Polycarbonate

Dimensions

300 x 230 x 85 mm, 9" x

11.8" x 3.3"

Weight

2.4 kg, 5.3 lb

Power

24 VDCMax 2.5WPower adapter & 10m cable included

Ingress Protection **IP65**

Head Office

NoiseMeters Ltd 7 Jayes Park Ockley Surrey RH5 5RR

Telephone +44 130 677 0855 Fax +44 845 680 0316

Email: info@noisemeters.com Support: support@noisemeters.com **Web Sites**

Main site:

https://eu.noisemeters.com

Product shortcut:

https://eu.noisemeters.com/p/se2ear-w/

Tech Support:

https://support.noisemeters.com